

## *Sliver brazed double row cup wheel*



### Specifications:

Item NO.	Diameter		Bore size(mm/inch)	Segment		Segment NO.
	mm	inch		width(mm)	height(mm)	
WS105SD	105	4"	16/22.23 5/8"/7/8"	5	7	8/8
WS115SD	115	4.3"	16/22.23 5/8"/7/8"	5	8	9/9
WS125SD	125	5"	16/22.23 5/8"/7/8"	5	8	9/9
WS150SD	150	6"	16/22.23 5/8"/7/8"	5	8	10/10
WS180SD	180	7"	16/22.23 5/8"/7/8"	5	8	12/12

### Contact us:

**XMF Tools Group**   
**Ad:** 312 YanZhao North Street  
ZhengDing County  
HeBei P R China  
**Post Code:** 050800  
**TEL:** 86-311-85174190  
85174259,85174229  
**FAX:** 86-311-85174239  
**E-mail:** xmf@xmftools.com

**Feature:** Sliver brazed double row cup wheel is ideal for beveling ,  
smoothing and shaping, excellent performance

**Application:** Granite, marble, concrete products, masonry material and  
all types of natural stone

**Machinery:** Angle grinder

**Different arbor sizes and segment specifications are available upon  
request**